



36" Explosion Proof Wall Exhaust & Intake Fans

Design performance:

- 12,300 CFM @ 0.25" SP c/w 2HP 230/460 Volt (usable on 208) 1150 RPM, 3 phase 60 Hz
- Note: Fan blades are adjustable pitch, so performance can be changed to a minimum of 9,300 CFM to a maximum of 19,200 CFM

Construction & Design Features:

Low motor RPM ensures quiet fan operation.

Fans are direct drive, therefore requiring no maintenance.

Adjust pitch, cast aluminum spark proof blades tested in accordance with AMCA standard 210.

Premium efficiency Teco/Westinghouse explosion proof motors.

- Motor is CSA certified, UL listed
- CSA certified for Class I, Div 1, Groups C & D; Class II, Div 1, Groups E, F & G
- T3B temperature code
- Invertor duty rated to 20:1 turndown

Heavy gauge steel fan panel with deep inlet venture, distributes air uniformly for efficient performance.

Full data packs are available upon request.

Options Available:

- Dampers/louvers - Weather hoods
- Thermostats - Guards

CALL YOUR LOCAL BRANCH FOR PRICING & AVAILABILITY

Inventory at time of print; 36 Exhaust fans and 40 Intake fans.



ALL UNITS COME WITH A 1 YEAR WARRANTY

Edmonton, AB

Calgary, AB

Winnipeg, MB

Surrey, BC

Vancouver, BC

780-423-4066

403-243-4130

204-775-8848

604-590-1667

604-566-9370